



SERTIFIKATAS

CERTIFICATE

No. FUR BSC 24-17

11 July 2024

Vilnius

Issued to **UAB NARBUTAS INTERNATIONAL**
Address **Ukmergės g. 308, LT-12110 Vilnius, Lithuania**
Product name **Office furniture. Work desks NOVA U, U SLIDE, A, O, H**
The list is given in Annex A
Manufacturer (name) **UAB NARBUTAS INTERNATIONAL**
Manufacturer address **Ukmergės g. 308, LT-12110 Vilnius, Lithuania**
Performance **EN 527-1:2011, EN 527-2:2016+A1:2019**
EN 1730:2012

Certification has been made according to the certification scheme 1b

Certificate has been issued according to the VSI FURNITEST Furniture testing centre testing reports No. BBC 23-108, dated Mart 21, 2023, No. BBC 24-264, dated July 2, 2024, No. BBC 24-265, dated July 8, 2024, No. BBC 24-266, dated July 11, 2024

The certificate is valid till 11 July 2026

Director



Jadvyga Mickienė

List of valid certificates: www.furnitest.com/furniture-certification

ANNEX A

Table 1. List of *Office furniture. Work desks NOVA U, U SLIDE, A, O, H* to the Certificate FUR BSC 24-17

Office desking		NOVA U						
Example	Description	Desktop type	Dimensions, mm			Item	EN 527-1	EN 527-2
			Width	Depth	Height			
	Desk	Plane	1000	600	740	DNA104-U	Not applicable	Applicable
			1200	600	740	DNA124-U	Not applicable	Applicable
			1400	600	740	DNA144-U	Not applicable	Applicable
			1600	600	740	DNA164-U	Not applicable	Applicable
			1200	700	740	DNA122-U	Not applicable	Applicable
			1400	700	740	DNA142-U	Not applicable	Applicable
			1600	700	740	DNA162-U	Not applicable	Applicable
			1800	700	740	DNA182-U	Not applicable	Applicable
			1200	800	740	DNA120-U	Type C	Applicable
			1400	800	740	DNA140-U	Type C	Applicable
			1600	800	740	DNA160-U	Type C	Applicable
			1800	800	740	DNA180-U	Type C	Applicable
			2000	800	740	DNA200-U	Type C	Applicable
		With grommet, L/H side	1400	600	740	DNA14E-U	Not applicable	Applicable
			1600	600	740	DNA16E-U	Not applicable	Applicable
			1400	700	740	DNA14M-U	Not applicable	Applicable
			1600	700	740	DNA16M-U	Not applicable	Applicable
			1800	700	740	DNA18M-U	Not applicable	Applicable
			1400	800	740	DNA14T-U	Type C	Applicable
			1600	800	740	DNA16T-U	Type C	Applicable
			1800	800	740	DNA18T-U	Type C	Applicable
			2000	800	740	DNA20T-U	Type C	Applicable
		With grommet, R/H side	1400	600	740	DNA14F-U	Not applicable	Applicable
			1600	600	740	DNA16F-U	Not applicable	Applicable
			1400	700	740	DNA14N-U	Not applicable	Applicable
			1600	700	740	DNA16N-U	Not applicable	Applicable
			1800	700	740	DNA18N-U	Not applicable	Applicable
			1400	800	740	DNA14U-U	Type C	Applicable
			1600	800	740	DNA16U-U	Type C	Applicable
			1800	800	740	DNA18U-U	Type C	Applicable
			2000	800	740	DNA20U-U	Type C	Applicable
		With grommet, middle position	1000	600	740	DNA10G-U	Not applicable	Applicable
			1200	600	740	DNA12G-U	Not applicable	Applicable
			1400	600	740	DNA14G-U	Not applicable	Applicable
			1600	600	740	DNA16G-U	Not applicable	Applicable
			1200	700	740	DNA123-U	Not applicable	Applicable
			1400	700	740	DNA143-U	Not applicable	Applicable

			1600	700	740	DNA163-U	Not applicable	Applicable
			1800	700	740	DNA183-U	Not applicable	Applicable
			1200	800	740	DNA121-U	Type C	Applicable
			1400	800	740	DNA141-U	Type C	Applicable
			1600	800	740	DNA161-U	Type C	Applicable
			1800	800	740	DNA181-U	Type C	Applicable
			2000	800	740	DNA201-U	Type C	Applicable
		With cut-out for cable port, L/H side	1400	600	740	DNA14H-U	Not applicable	Applicable
			1600	600	740	DNA16H-U	Not applicable	Applicable
			1400	700	740	DNA14P-U	Not applicable	Applicable
			1600	700	740	DNA16P-U	Not applicable	Applicable
			1800	700	740	DNA18P-U	Not applicable	Applicable
			1400	800	740	DNA14V-U	Type C	Applicable
			1600	800	740	DNA16V-U	Type C	Applicable
			1800	800	740	DNA18V-U	Type C	Applicable
			2000	800	740	DNA20V-U	Type C	Applicable
		With cut-out for cable port, R/H side	1400	600	740	DNA14J-U	Not applicable	Applicable
			1600	600	740	DNA16J-U	Not applicable	Applicable
			1400	700	740	DNA14R-U	Not applicable	Applicable
			1600	700	740	DNA16R-U	Not applicable	Applicable
			1800	700	740	DNA18R-U	Not applicable	Applicable
			1400	800	740	DNA14Y-U	Type C	Applicable
			1600	800	740	DNA16Y-U	Type C	Applicable
			1800	800	740	DNA18Y-U	Type C	Applicable
			2000	800	740	DNA20Y-U	Type C	Applicable
		With cut-out for cable port, R/H and L/H sides	1400	600	740	DNA14X-U	Not applicable	Applicable
			1600	600	740	DNA16X-U	Not applicable	Applicable
			1400	700	740	DNA14W-U	Not applicable	Applicable
			1600	700	740	DNA16W-U	Not applicable	Applicable
			1800	700	740	DNA18W-U	Not applicable	Applicable
			1400	800	740	DNA14Q-U	Type C	Applicable
			1600	800	740	DNA16Q-U	Type C	Applicable
			1800	800	740	DNA18Q-U	Type C	Applicable
			2000	800	740	DNA20Q-U	Type C	Applicable
		With cut-out for cable port, middle position	1000	600	740	DNA10K-U	Not applicable	Applicable
			1200	600	740	DNA12K-U	Not applicable	Applicable
			1400	600	740	DNA14K-U	Not applicable	Applicable
			1600	600	740	DNA16K-U	Not applicable	Applicable
			1200	700	740	DNA12S-U	Not applicable	Applicable
			1400	700	740	DNA14S-U	Not applicable	Applicable
			1600	700	740	DNA16S-U	Not applicable	Applicable
			1800	700	740	DNA18S-U	Not applicable	Applicable
			1200	800	740	DNA12Z-U	Type C	Applicable
			1400	800	740	DNA14Z-U	Type C	Applicable

			1600	800	740	DNA16Z-U	Type C	Applicable
			1800	800	740	DNA18Z-U	Type C	Applicable
			2000	800	740	DNA20Z-U	Type C	Applicable
		With scallop	1000	600	740	DNA10L-U	Not applicable	Applicable
			1200	600	740	DNA12L-U	Not applicable	Applicable
			1400	600	740	DNA14L-U	Not applicable	Applicable
			1600	600	740	DNA16L-U	Not applicable	Applicable
			1200	700	740	DNA126-U	Not applicable	Applicable
			1400	700	740	DNA146-U	Not applicable	Applicable
			1600	700	740	DNA166-U	Not applicable	Applicable
			1800	700	740	DNA186-U	Not applicable	Applicable
			1200	800	740	DNA125-U	Type C	Applicable
			1400	800	740	DNA145-U	Type C	Applicable
			1600	800	740	DNA165-U	Type C	Applicable
			1800	800	740	DNA185-U	Type C	Applicable
			2000	800	740	DNA205-U	Type C	Applicable
	Single row 2-desk bench	Plane	2400	800	740	DNS24A-U	Type C	Applicable
			2800	800	740	DNS28A-U	Type C	Applicable
			3200	800	740	DNS32A-U	Type C	Applicable
			3600	800	740	DNS36A-U	Type C	Applicable
		With grommet, L/H side	2800	800	740	DNS28C-U	Type C	Applicable
			3200	800	740	DNS32C-U	Type C	Applicable
			3600	800	740	DNS36C-U	Type C	Applicable
		With grommet, R/H side	2800	800	740	DNS28D-U	Type C	Applicable
			3200	800	740	DNS32D-U	Type C	Applicable
			3600	800	740	DNS36D-U	Type C	Applicable
		With grommet, middle position	2400	800	740	DNS24B-U	Type C	Applicable
			2800	800	740	DNS28B-U	Type C	Applicable
			3200	800	740	DNS32B-U	Type C	Applicable
		With cut-out for cable port, L/H side	3600	800	740	DNS36B-U	Type C	Applicable
			2800	800	740	DNS28E-U	Type C	Applicable
			3200	800	740	DNS32E-U	Type C	Applicable
		With cut-out for cable port, R/H side	3600	800	740	DNS36E-U	Type C	Applicable
			2800	800	740	DNS28F-U	Type C	Applicable
			3200	800	740	DNS32F-U	Type C	Applicable
		With cut-out for cable port, R/H and L/H sides	3600	800	740	DNS36F-U	Type C	Applicable
			2800	800	740	DNS28U-U	Type C	Applicable
			3200	800	740	DNS32U-U	Type C	Applicable
		With cut-out for cable port, middle position	3600	800	740	DNS36U-U	Type C	Applicable
			2400	800	740	DNS24G-U	Type C	Applicable
			2800	800	740	DNS28G-U	Type C	Applicable
			3200	800	740	DNS32G-U	Type C	Applicable
		With scallop	3600	800	740	DNS36G-U	Type C	Applicable
			2400	800	740	DNS248-U	Type C	Applicable
			2800	800	740	DNS288-U	Type C	Applicable
			3200	800	740	DNS328-U	Type C	Applicable
	Supplementary unit for single row 2-desk bench	Plane	3600	800	740	DNS368-U	Type C	Applicable
			1200	800	740	DND12A-U	Type C	Applicable
			1400	800	740	DND14A-U	Type C	Applicable
			1600	800	740	DND16A-U	Type C	Applicable

			1800	800	740	DND18A-U	Type C	Applicable
		With grommet, L/H side	1400	800	740	DND14C-U	Type C	Applicable
			1600	800	740	DND16C-U	Type C	Applicable
			1800	800	740	DND18C-U	Type C	Applicable
		With grommet, R/H side	1400	800	740	DND14D-U	Type C	Applicable
			1600	800	740	DND16D-U	Type C	Applicable
			1800	800	740	DND18D-U	Type C	Applicable
		With grommet, middle position	1200	800	740	DND12B-U	Type C	Applicable
			1400	800	740	DND14B-U	Type C	Applicable
			1600	800	740	DND16B-U	Type C	Applicable
		With cut-out for cable port, L/H side	1800	800	740	DND18B-U	Type C	Applicable
			1400	800	740	DND14E-U	Type C	Applicable
			1600	800	740	DND16E-U	Type C	Applicable
		With cut-out for cable port, R/H side	1800	800	740	DND18E-U	Type C	Applicable
			1400	800	740	DND14F-U	Type C	Applicable
			1600	800	740	DND16F-U	Type C	Applicable
		With cut-out for cable port, R/H and L/H sides	1800	800	740	DND18F-U	Type C	Applicable
			1400	800	740	DND14U-U	Type C	Applicable
			1600	800	740	DND16U-U	Type C	Applicable
		With cut-out for cable port, middle position	1800	800	740	DND18U-U	Type C	Applicable
			1200	800	740	DND12G-U	Type C	Applicable
			1400	800	740	DND14G-U	Type C	Applicable
		With scallop	1600	800	740	DND16G-U	Type C	Applicable
			1800	800	740	DND18G-U	Type C	Applicable
			1200	800	740	DND128-U	Type C	Applicable
			1400	800	740	DND148-U	Type C	Applicable
			1600	800	740	DND168-U	Type C	Applicable
			1800	800	740	DND188-U	Type C	Applicable
	2-desk bench	Plane	1000	1240	740	D2S100-U	Not applicable	Applicable
			1200	1240	740	D2S120-U	Not applicable	Applicable
			1400	1240	740	D2S140-U	Not applicable	Applicable
			1600	1240	740	D2S160-U	Not applicable	Applicable
			1200	1440	740	DNS123-U	Not applicable	Applicable
			1400	1440	740	DNS143-U	Not applicable	Applicable
			1600	1440	740	DNS163-U	Not applicable	Applicable
			1800	1440	740	DNS183-U	Not applicable	Applicable
			1200	1640	740	DNS122-U	Type C	Applicable
			1400	1640	740	DNS142-U	Type C	Applicable
			1600	1640	740	DNS162-U	Type C	Applicable
			1800	1640	740	DNS182-U	Type C	Applicable
			2000	1640	740	DNS202-U	Type C	Applicable
		With grommet, L/H side	1400	1240	740	D2S141-U	Not applicable	Applicable
			1600	1240	740	D2S161-U	Not applicable	Applicable
			1400	1440	740	DNS14H-U	Not applicable	Applicable
			1600	1440	740	DNS16H-U	Not applicable	Applicable
			1800	1440	740	DNS18H-U	Not applicable	Applicable
			1400	1640	740	DNS14N-U	Type C	Applicable
			1600	1640	740	DNS16N-U	Type C	Applicable
			1800	1640	740	DNS18N-U	Type C	Applicable

			2000	1640	740	DNS20N-U	Type C	Applicable
		With grommet, R/H side	1400	1240	740	D2S142-U	Not applicable	Applicable
			1600	1240	740	D2S162-U	Not applicable	Applicable
			1400	1440	740	DNS14J-U	Not applicable	Applicable
			1600	1440	740	DNS16J-U	Not applicable	Applicable
			1800	1440	740	DNS18J-U	Not applicable	Applicable
			1400	1640	740	DNS14P-U	Type C	Applicable
			1600	1640	740	DNS16P-U	Type C	Applicable
			1800	1640	740	DNS18P-U	Type C	Applicable
			2000	1640	740	DNS20P-U	Type C	Applicable
		With grommet, middle position	1000	1240	740	D2S103-U	Not applicable	Applicable
			1200	1240	740	D2S123-U	Not applicable	Applicable
			1400	1240	740	D2S143-U	Not applicable	Applicable
			1600	1240	740	D2S163-U	Not applicable	Applicable
			1200	1440	740	DNS125-U	Not applicable	Applicable
			1400	1440	740	DNS145-U	Not applicable	Applicable
			1600	1440	740	DNS165-U	Not applicable	Applicable
			1800	1440	740	DNS185-U	Not applicable	Applicable
			1200	1640	740	DNS124-U	Type C	Applicable
			1400	1640	740	DNS144-U	Type C	Applicable
			1600	1640	740	DNS164-U	Type C	Applicable
			1800	1640	740	DNS184-U	Type C	Applicable
			2000	1640	740	DNS204-U	Type C	Applicable
		With cut-out for cable port, L/H side	1400	1240	740	D2S144-U	Not applicable	Applicable
			1600	1240	740	D2S164-U	Not applicable	Applicable
			1400	1440	740	DNS14K-U	Not applicable	Applicable
			1600	1440	740	DNS16K-U	Not applicable	Applicable
			1800	1440	740	DNS18K-U	Not applicable	Applicable
			1400	1640	740	DNS14R-U	Type C	Applicable
			1600	1640	740	DNS16R-U	Type C	Applicable
			1800	1640	740	DNS18R-U	Type C	Applicable
			2000	1640	740	DNS20R-U	Type C	Applicable
		With cut-out for cable port, R/H side	1400	1240	740	D2S145-U	Not applicable	Applicable
			1600	1240	740	D2S165-U	Not applicable	Applicable
			1400	1440	740	DNS14L-U	Not applicable	Applicable
			1600	1440	740	DNS16L-U	Not applicable	Applicable
			1800	1440	740	DNS18L-U	Not applicable	Applicable
			1400	1640	740	DNS14S-U	Type C	Applicable
			1600	1640	740	DNS16S-U	Type C	Applicable
			1800	1640	740	DNS18S-U	Type C	Applicable
			2000	1640	740	DNS20S-U	Type C	Applicable
		With cut-out for cable port, R/H and L/H sides	1400	1240	740	D2S148-U	Not applicable	Applicable
			1600	1240	740	D2S168-U	Not applicable	Applicable
			1400	1440	740	DNS14V-U	Not applicable	Applicable

			1600	1440	740	DNS16V-U	Not applicable	Applicable
			1800	1440	740	DNS18V-U	Not applicable	Applicable
			1400	1640	740	DNS14Z-U	Type C	Applicable
			1600	1640	740	DNS16Z-U	Type C	Applicable
			1800	1640	740	DNS18Z-U	Type C	Applicable
			2000	1640	740	DNS20Z-U	Type C	Applicable
		With cut-out for cable port, middle position	1000	1240	740	D2S106-U	Not applicable	Applicable
			1200	1240	740	D2S126-U	Not applicable	Applicable
			1400	1240	740	D2S146-U	Not applicable	Applicable
			1600	1240	740	D2S166-U	Not applicable	Applicable
			1200	1440	740	DNS12M-U	Not applicable	Applicable
			1400	1440	740	DNS14M-U	Not applicable	Applicable
			1600	1440	740	DNS16M-U	Not applicable	Applicable
			1800	1440	740	DNS18M-U	Not applicable	Applicable
			1200	1640	740	DNS12T-U	Type C	Applicable
			1400	1640	740	DNS14T-U	Type C	Applicable
			1600	1640	740	DNS16T-U	Type C	Applicable
			1800	1640	740	DNS18T-U	Type C	Applicable
			2000	1640	740	DNS20T-U	Type C	Applicable
		With scallop	1000	1240	740	D2S107-U	Not applicable	Applicable
			1200	1240	740	D2S127-U	Not applicable	Applicable
			1400	1240	740	D2S147-U	Not applicable	Applicable
			1600	1240	740	D2S167-U	Not applicable	Applicable
			1200	1440	740	DNS127-U	Not applicable	Applicable
			1400	1440	740	DNS147-U	Not applicable	Applicable
			1600	1440	740	DNS167-U	Not applicable	Applicable
			1800	1440	740	DNS187-U	Not applicable	Applicable
			1200	1640	740	DNS126-U	Type C	Applicable
			1400	1640	740	DNS146-U	Type C	Applicable
			1600	1640	740	DNS166-U	Type C	Applicable
			1800	1640	740	DNS186-U	Type C	Applicable
			2000	1640	740	DNS206-U	Type C	Applicable
	4-desk bench	Plane	2400	1440	740	DNS243-U	Not applicable	Applicable
			2800	1440	740	DNS283-U	Not applicable	Applicable
			3200	1440	740	DNS323-U	Not applicable	Applicable
			3600	1440	740	DNS363-U	Not applicable	Applicable
			2400	1640	740	DNS242-U	Type C	Applicable
			2800	1640	740	DNS282-U	Type C	Applicable
			3200	1640	740	DNS322-U	Type C	Applicable
			3600	1640	740	DNS362-U	Type C	Applicable
		With grommet, L/H side	2800	1440	740	D4S280-U	Not applicable	Applicable
			3200	1440	740	D4S320-U	Not applicable	Applicable
			3600	1440	740	D4S360-U	Not applicable	Applicable
			2800	1640	740	D4S285-U	Type C	Applicable

			3200	1640	740	D4S325-U	Type C	Applicable
			3600	1640	740	D4S365-U	Type C	Applicable
		With grommet, R/H side	2800	1440	740	D4S281-U	Not applicable	Applicable
			3200	1440	740	D4S321-U	Not applicable	Applicable
			3600	1440	740	D4S361-U	Not applicable	Applicable
			2800	1640	740	D4S286-U	Type C	Applicable
			3200	1640	740	D4S326-U	Type C	Applicable
			3600	1640	740	D4S366-U	Type C	Applicable
		With grommet, middle position	2400	1440	740	DNS245-U	Not applicable	Applicable
			2800	1440	740	DNS285-U	Not applicable	Applicable
			3200	1440	740	DNS325-U	Not applicable	Applicable
			3600	1440	740	DNS365-U	Not applicable	Applicable
			2400	1640	740	DNS244-U	Type C	Applicable
			2800	1640	740	DNS284-U	Type C	Applicable
			3200	1640	740	DNS324-U	Type C	Applicable
			3600	1640	740	DNS364-U	Type C	Applicable
		With cut-out for cable port, L/H side	2800	1440	740	D4S282-U	Not applicable	Applicable
			3200	1440	740	D4S322-U	Not applicable	Applicable
			3600	1440	740	D4S362-U	Not applicable	Applicable
			2800	1640	740	D4S287-U	Type C	Applicable
			3200	1640	740	D4S327-U	Type C	Applicable
			3600	1640	740	D4S367-U	Type C	Applicable
		With cut-out for cable port, R/H side	2800	1440	740	D4S283-U	Not applicable	Applicable
			3200	1440	740	D4S323-U	Not applicable	Applicable
			3600	1440	740	D4S363-U	Not applicable	Applicable
			2800	1640	740	D4S288-U	Type C	Applicable
			3200	1640	740	D4S328-U	Type C	Applicable
			3600	1640	740	D4S368-U	Type C	Applicable
		With cut-out for cable port, R/H and L/H sides	2800	1440	740	D4S28A-U	Not applicable	Applicable
			3200	1440	740	D4S32A-U	Not applicable	Applicable
			3600	1440	740	D4S36A-U	Not applicable	Applicable
			2800	1640	740	D4S28B-U	Type C	Applicable
			3200	1640	740	D4S32B-U	Type C	Applicable
			3600	1640	740	D4S36B-U	Type C	Applicable
		With cut-out for cable port, middle position	2400	1440	740	D4S244-U	Not applicable	Applicable
			2800	1440	740	D4S284-U	Not applicable	Applicable
			3200	1440	740	D4S324-U	Not applicable	Applicable
			3600	1440	740	D4S364-U	Not applicable	Applicable
			2400	1640	740	D4S249-U	Type C	Applicable
			2800	1640	740	D4S289-U	Type C	Applicable
			3200	1640	740	D4S329-U	Type C	Applicable
			3600	1640	740	D4S369-U	Type C	Applicable
		With scallop	2400	1440	740	DNS249-U	Not applicable	Applicable
			2800	1440	740	DNS289-U	Not applicable	Applicable
			3200	1440	740	DNS329-U	Not applicable	Applicable

			3600	1440	740	DNS369-U	Not applicable	Applicable
			2400	1640	740	DNS247-U	Type C	Applicable
			2800	1640	740	DNS287-U	Type C	Applicable
			3200	1640	740	DNS327-U	Type C	Applicable
			3600	1640	740	DNS367-U	Type C	Applicable
	Supplementary unit for desk benches	Plane	1200	1440	740	DND123-U	Not applicable	Applicable
			1400	1440	740	DND143-U	Not applicable	Applicable
			1600	1440	740	DND163-U	Not applicable	Applicable
			1800	1440	740	DND183-U	Not applicable	Applicable
			1200	1640	740	DND122-U	Type C	Applicable
			1400	1640	740	DND142-U	Type C	Applicable
			1600	1640	740	DND162-U	Type C	Applicable
			1800	1640	740	DND182-U	Type C	Applicable
		With grommet, L/H side	1400	1440	740	DND14H-U	Not applicable	Applicable
			1600	1440	740	DND16H-U	Not applicable	Applicable
			1800	1440	740	DND18H-U	Not applicable	Applicable
			1400	1640	740	DND14N-U	Type C	Applicable
			1600	1640	740	DND16N-U	Type C	Applicable
			1800	1640	740	DND18N-U	Type C	Applicable
		With grommet, R/H side	1400	1440	740	DND14J-U	Not applicable	Applicable
			1600	1440	740	DND16J-U	Not applicable	Applicable
			1800	1440	740	DND18J-U	Not applicable	Applicable
			1400	1640	740	DND14P-U	Type C	Applicable
			1600	1640	740	DND16P-U	Type C	Applicable
			1800	1640	740	DND18P-U	Type C	Applicable
		With grommet, middle position	1200	1440	740	DND125-U	Not applicable	Applicable
			1400	1440	740	DND145-U	Not applicable	Applicable
			1600	1440	740	DND165-U	Not applicable	Applicable
			1800	1440	740	DND185-U	Not applicable	Applicable
			1200	1640	740	DND124-U	Type C	Applicable
			1400	1640	740	DND144-U	Type C	Applicable
			1600	1640	740	DND164-U	Type C	Applicable
			1800	1640	740	DND184-U	Type C	Applicable
		With cut-out for cable port, L/H side	1400	1440	740	DND14K-U	Not applicable	Applicable
			1600	1440	740	DND16K-U	Not applicable	Applicable
			1800	1440	740	DND18K-U	Not applicable	Applicable
			1400	1640	740	DND14R-U	Type C	Applicable
			1600	1640	740	DND16R-U	Type C	Applicable
			1800	1640	740	DND18R-U	Type C	Applicable
		With cut-out for cable port, R/H side	1400	1440	740	DND14L-U	Not applicable	Applicable
			1600	1440	740	DND16L-U	Not applicable	Applicable
			1800	1440	740	DND18L-U	Not applicable	Applicable
			1400	1640	740	DND14S-U	Type C	Applicable
			1600	1640	740	DND16S-U	Type C	Applicable
			1800	1640	740	DND18S-U	Type C	Applicable
			1400	1440	740	DND14V-U	Not applicable	Applicable

		With cut-out for cable port, R/H and L/H sides	1600	1440	740	DND16V-U	Not applicable	Applicable
			1800	1440	740	DND18V-U	Not applicable	Applicable
			1400	1640	740	DND14Z-U	Type C	Applicable
			1600	1640	740	DND16Z-U	Type C	Applicable
			1800	1640	740	DND18Z-U	Type C	Applicable
		With cut-out for cable port, middle position	1200	1440	740	DND12M-U	Not applicable	Applicable
			1400	1440	740	DND14M-U	Not applicable	Applicable
			1600	1440	740	DND16M-U	Not applicable	Applicable
			1800	1440	740	DND18M-U	Not applicable	Applicable
			1200	1640	740	DND12T-U	Type C	Applicable
			1400	1640	740	DND14T-U	Type C	Applicable
			1600	1640	740	DND16T-U	Type C	Applicable
			1800	1640	740	DND18T-U	Type C	Applicable
		With scallop	1200	1440	740	DND129-U	Not applicable	Applicable
			1400	1440	740	DND149-U	Not applicable	Applicable
			1600	1440	740	DND169-U	Not applicable	Applicable
			1800	1440	740	DND189-U	Not applicable	Applicable
			1200	1640	740	DND127-U	Type C	Applicable
			1400	1640	740	DND147-U	Type C	Applicable
			1600	1640	740	DND167-U	Type C	Applicable
			1800	1640	740	DND187-U	Type C	Applicable
	End of bench desk	Plane	1240	600	740	DNE120-U	Not applicable	Applicable
			1440	700	740	DNE140-U	Not applicable	Applicable
			1640	800	740	DNE160-U	Type C	Applicable
		With grommet, L/H side	1440	700	740	DNE141-U	Not applicable	Applicable
			1640	800	740	DNE161-U	Type C	Applicable
		With grommet, R/H side	1440	700	740	DNE142-U	Not applicable	Applicable
			1640	800	740	DNE162-U	Type C	Applicable
		With grommet, middle position	1240	600	740	DNE123-U	Not applicable	Applicable
			1440	700	740	DNE143-U	Not applicable	Applicable
			1640	800	740	DNE163-U	Type C	Applicable
		With cut-out for cable port, L/H side	1440	700	740	DNE144-U	Not applicable	Applicable
			1640	800	740	DNE164-U	Type C	Applicable
		With cut-out for cable port, R/H side	1440	700	740	DNE145-U	Not applicable	Applicable
			1640	800	740	DNE165-U	Type C	Applicable
		With cut-out for cable port, R/H and L/H sides	1440	700	740	DNE148-U	Not applicable	Applicable
			1640	800	740	DNE168-U	Type C	Applicable
		With cut-out for cable port, middle position	1240	600	740	DNE126-U	Not applicable	Applicable
			1440	700	740	DNE146-U	Not applicable	Applicable
			1640	800	740	DNE166-U	Type C	Applicable
		With scallop	1240	600	740	DNE127-U	Not applicable	Applicable
			1440	700	740	DNE147-U	Not applicable	Applicable
			1640	800	740	DNE167-U	Type C	Applicable
	Crescent desk	Plane, L/H side	1400	1200	740	DNL140-U	Type C	Applicable
			1600	1200	740	DNL160-U	Type C	Applicable

			1800	1200	740	DNL180-U	Type C	Applicable
		With grommet, L/H side	1400	1200	740	DNL141-U	Type C	Applicable
			1600	1200	740	DNL161-U	Type C	Applicable
			1800	1200	740	DNL181-U	Type C	Applicable
			1800	1200	740	DNL181-U	Type C	Applicable
		With cut-out for cable port, L/H side	1400	1200	740	DNL144-U	Type C	Applicable
			1600	1200	740	DNL164-U	Type C	Applicable
			1800	1200	740	DNL184-U	Type C	Applicable
		Plane, R/H side	1400	1200	740	DNR140-U	Type C	Applicable
			1600	1200	740	DNR160-U	Type C	Applicable
			1800	1200	740	DNR180-U	Type C	Applicable
		With grommet, R/H side	1400	1200	740	DNR141-U	Type C	Applicable
			1600	1200	740	DNR161-U	Type C	Applicable
			1800	1200	740	DNR181-U	Type C	Applicable
		With cut-out for cable port, R/H side	1400	1200	740	DNR144-U	Type C	Applicable
			1600	1200	740	DNR164-U	Type C	Applicable
			1800	1200	740	DNR184-U	Type C	Applicable
	3-desk bench	With scallop	Ø 2810	Ø 2810	740	DNS128-U	Type C	Applicable
	Supplementary unit - return table	Plane	800	600	740	DNC080-U	Not applicable	Applicable
		Plane	600	800	740	DNC060-U	Not applicable	Applicable
	Supplementary unit - return table for desk benches	Plane	1640	600	740	DNC161-U	Not applicable	Applicable
		Plane	1440	600	740	DNC141-U	Not applicable	Applicable

Office desking			NOVA U SLIDE					
Example	Description	Desktop type	Dimensions, mm			Item	EN 527-1	EN 527-2
			Width	Depth	Height			
	Desk with sliding desktop	Plane	1400	700	743	DNA151-U	Not applicable	Applicable
			1600	700	743	DNA171-U	Not applicable	Applicable
			1400	800	743	DNA153-U	Type C	Applicable
			1600	800	743	DNA173-U	Type C	Applicable
		With scallop	1400	700	743	DNA152-U	Not applicable	Applicable
			1600	700	743	DNA172-U	Not applicable	Applicable
			1400	800	743	DNA154-U	Type C	Applicable
			1600	800	743	DNA174-U	Type C	Applicable
	2-desk bench with sliding desktops	Plane	1400	1440	743	DNS150-U	Not applicable	Applicable
			1600	1440	743	DNS170-U	Not applicable	Applicable
			1400	1640	743	DNS152-U	Type C	Applicable
			1600	1640	743	DNS172-U	Type C	Applicable
		With scallop	1400	1440	743	DNS151-U	Not applicable	Applicable
			1600	1440	743	DNS171-U	Not applicable	Applicable
			1400	1640	743	DNS153-U	Type C	Applicable
			1600	1640	743	DNS173-U	Type C	Applicable
	4-desk bench with sliding desktops	Plane	2800	1440	743	DNS292-U	Not applicable	Applicable
			3200	1440	743	DNS332-U	Not applicable	Applicable
			2800	1640	743	DNS294-U	Type C	Applicable
			3200	1640	743	DNS334-U	Type C	Applicable
		With scallop	2800	1440	743	DNS293-U	Not applicable	Applicable
			3200	1440	743	DNS333-U	Not applicable	Applicable
			2800	1640	743	DNS295-U	Type C	Applicable
			3200	1640	743	DNS335-U	Type C	Applicable
	Supplementary unit for desk benches with sliding desktops	Plane	1400	1440	743	DND152-U	Not applicable	Applicable
			1600	1440	743	DND172-U	Not applicable	Applicable
			1400	1640	743	DND154-U	Type C	Applicable
			1600	1640	743	DND174-U	Type C	Applicable
		With scallop	1400	1440	743	DND153-U	Not applicable	Applicable
			1600	1440	743	DND173-U	Not applicable	Applicable
			1400	1640	743	DND155-U	Type C	Applicable
			1600	1640	743	DND175-U	Type C	Applicable

Office desking		NOVA A						
Example	Description	Desktop type	Dimensions, mm			Item	EN 527-1	EN 527-2
			Width	Depth	Height			
	Desk	Plane	1000	600	740	DNA104-A	Not applicable	Applicable
			1200	600	740	DNA124-A	Not applicable	Applicable
			1400	600	740	DNA144-A	Not applicable	Applicable
			1600	600	740	DNA164-A	Not applicable	Applicable
			1200	700	740	DNA122-A	Not applicable	Applicable
			1400	700	740	DNA142-A	Not applicable	Applicable
			1600	700	740	DNA162-A	Not applicable	Applicable
			1800	700	740	DNA182-A	Not applicable	Applicable
			1200	800	740	DNA120-A	Type C	Applicable
			1400	800	740	DNA140-A	Type C	Applicable
			1600	800	740	DNA160-A	Type C	Applicable
			1800	800	740	DNA180-A	Type C	Applicable
			2000	800	740	DNA200-A	Type C	Applicable
		With grommet, L/H side	1400	600	740	DNA14E-A	Not applicable	Applicable
			1600	600	740	DNA16E-A	Not applicable	Applicable
			1400	700	740	DNA14M-A	Not applicable	Applicable
			1600	700	740	DNA16M-A	Not applicable	Applicable
			1800	700	740	DNA18M-A	Not applicable	Applicable
			1400	800	740	DNA14T-A	Type C	Applicable
			1600	800	740	DNA16T-A	Type C	Applicable
			1800	800	740	DNA18T-A	Type C	Applicable
			2000	800	740	DNA20T-A	Type C	Applicable
		With grommet, R/H side	1400	600	740	DNA14F-A	Not applicable	Applicable
			1600	600	740	DNA16F-A	Not applicable	Applicable
			1400	700	740	DNA14N-A	Not applicable	Applicable
			1600	700	740	DNA16N-A	Not applicable	Applicable
			1800	700	740	DNA18N-A	Not applicable	Applicable
			1400	800	740	DNA14U-A	Type C	Applicable
			1600	800	740	DNA16U-A	Type C	Applicable
			1800	800	740	DNA18U-A	Type C	Applicable
			2000	800	740	DNA20U-A	Type C	Applicable
		With grommet, middle position	1000	600	740	DNA10G-A	Not applicable	Applicable
			1200	600	740	DNA12G-A	Not applicable	Applicable
			1400	600	740	DNA14G-A	Not applicable	Applicable
			1600	600	740	DNA16G-A	Not applicable	Applicable
			1200	700	740	DNA123-A	Not applicable	Applicable

			1400	700	740	DNA143-A	Not applicable	Applicable
			1600	700	740	DNA163-A	Not applicable	Applicable
			1800	700	740	DNA183-A	Not applicable	Applicable
			1200	800	740	DNA121-A	Type C	Applicable
			1400	800	740	DNA141-A	Type C	Applicable
			1600	800	740	DNA161-A	Type C	Applicable
			1800	800	740	DNA181-A	Type C	Applicable
			2000	800	740	DNA201-A	Type C	Applicable
		With cut-out for cable port, L/H side	1400	600	740	DNA14H-A	Not applicable	Applicable
			1600	600	740	DNA16H-A	Not applicable	Applicable
			1400	700	740	DNA14P-A	Not applicable	Applicable
			1600	700	740	DNA16P-A	Not applicable	Applicable
			1800	700	740	DNA18P-A	Not applicable	Applicable
			1400	800	740	DNA14V-A	Type C	Applicable
			1600	800	740	DNA16V-A	Type C	Applicable
			1800	800	740	DNA18V-A	Type C	Applicable
			2000	800	740	DNA20V-A	Type C	Applicable
		With cut-out for cable port, R/H side	1400	600	740	DNA14J-A	Not applicable	Applicable
			1600	600	740	DNA16J-A	Not applicable	Applicable
			1400	700	740	DNA14R-A	Not applicable	Applicable
			1600	700	740	DNA16R-A	Not applicable	Applicable
			1800	700	740	DNA18R-A	Not applicable	Applicable
			1400	800	740	DNA14Y-A	Type C	Applicable
			1600	800	740	DNA16Y-A	Type C	Applicable
			1800	800	740	DNA18Y-A	Type C	Applicable
			2000	800	740	DNA20Y-A	Type C	Applicable
		With cut-out for cable port, R/H and L/H sides	1400	600	740	DNA14X-A	Not applicable	Applicable
			1600	600	740	DNA16X-A	Not applicable	Applicable
			1400	700	740	DNA14W-A	Not applicable	Applicable
			1600	700	740	DNA16W-A	Not applicable	Applicable
			1800	700	740	DNA18W-A	Not applicable	Applicable
			1400	800	740	DNA14Q-A	Type C	Applicable
			1600	800	740	DNA16Q-A	Type C	Applicable
			1800	800	740	DNA18Q-A	Type C	Applicable
			2000	800	740	DNA20Q-A	Type C	Applicable
		With cut-out for cable port, middle position	1000	600	740	DNA10K-A	Not applicable	Applicable
			1200	600	740	DNA12K-A	Not applicable	Applicable
			1400	600	740	DNA14K-A	Not applicable	Applicable
			1600	600	740	DNA16K-A	Not applicable	Applicable

			1200	700	740	DNA12S-A	Not applicable	Applicable
			1400	700	740	DNA14S-A	Not applicable	Applicable
			1600	700	740	DNA16S-A	Not applicable	Applicable
			1800	700	740	DNA18S-A	Not applicable	Applicable
			1200	800	740	DNA12Z-A	Type C	Applicable
			1400	800	740	DNA14Z-A	Type C	Applicable
			1600	800	740	DNA16Z-A	Type C	Applicable
			1800	800	740	DNA18Z-A	Type C	Applicable
			2000	800	740	DNA20Z-A	Type C	Applicable
		With scallop	1000	600	740	DNA10L-A	Not applicable	Applicable
			1200	600	740	DNA12L-A	Not applicable	Applicable
			1400	600	740	DNA14L-A	Not applicable	Applicable
			1600	600	740	DNA16L-A	Not applicable	Applicable
			1200	700	740	DNA126-A	Not applicable	Applicable
			1400	700	740	DNA146-A	Not applicable	Applicable
			1600	700	740	DNA166-A	Not applicable	Applicable
			1800	700	740	DNA186-A	Not applicable	Applicable
			1200	800	740	DNA125-A	Type C	Applicable
			1400	800	740	DNA145-A	Type C	Applicable
	Single row 2-desk bench	Plane	2400	800	740	DNS24A-A	Type C	Applicable
			2800	800	740	DNS28A-A	Type C	Applicable
			3200	800	740	DNS32A-A	Type C	Applicable
			3600	800	740	DNS36A-A	Type C	Applicable
		With grommet, L/H side	2800	800	740	DNS28C-A	Type C	Applicable
			3200	800	740	DNS32C-A	Type C	Applicable
			3600	800	740	DNS36C-A	Type C	Applicable
		With grommet, R/H side	2800	800	740	DNS28D-A	Type C	Applicable
			3200	800	740	DNS32D-A	Type C	Applicable
			3600	800	740	DNS36D-A	Type C	Applicable
		With grommet, middle position	2400	800	740	DNS241-A	Type C	Applicable
			2800	800	740	DNS281-A	Type C	Applicable
			3200	800	740	DNS321-A	Type C	Applicable
			3600	800	740	DNS361-A	Type C	Applicable
		With cut-out for cable port, L/H side	2800	800	740	DNS28E-A	Type C	Applicable
			3200	800	740	DNS32E-A	Type C	Applicable

			3600	800	740	DNS36E-A	Type C	Applicable
		With cut-out for cable port, R/H side	2800	800	740	DNS28F-A	Type C	Applicable
			3200	800	740	DNS32F-A	Type C	Applicable
			3600	800	740	DNS36F-A	Type C	Applicable
		With cut-out for cable port, R/H and L/H sides	2800	800	740	DNS28U-A	Type C	Applicable
			3200	800	740	DNS32U-A	Type C	Applicable
			3600	800	740	DNS36U-A	Type C	Applicable
		With cut-out for cable port, middle position	2400	800	740	DNS24G-A	Type C	Applicable
			2800	800	740	DNS28G-A	Type C	Applicable
			3200	800	740	DNS32G-A	Type C	Applicable
			3600	800	740	DNS36G-A	Type C	Applicable
		With scallop	2400	800	740	DNS246-A	Type C	Applicable
			2800	800	740	DNS286-A	Type C	Applicable
			3200	800	740	DNS326-A	Type C	Applicable
			3600	800	740	DNS366-A	Type C	Applicable
	Supplementary unit for single row 2-desk bench	Plane	1200	800	740	DND12A-A	Type C	Applicable
			1400	800	740	DND14A-A	Type C	Applicable
			1600	800	740	DND16A-A	Type C	Applicable
			1800	800	740	DND18A-A	Type C	Applicable
		With grommet, L/H side	1400	800	740	DND14C-A	Type C	Applicable
			1600	800	740	DND16C-A	Type C	Applicable
			1800	800	740	DND18C-A	Type C	Applicable
		With grommet, R/H side	1400	800	740	DND14D-A	Type C	Applicable
			1600	800	740	DND16D-A	Type C	Applicable
			1800	800	740	DND18D-A	Type C	Applicable
		With grommet, middle position	1200	800	740	DND121-A	Type C	Applicable
			1400	800	740	DND141-A	Type C	Applicable
			1600	800	740	DND161-A	Type C	Applicable
			1800	800	740	DND181-A	Type C	Applicable
		With cut-out for cable port, L/H side	1400	800	740	DND14E-A	Type C	Applicable
			1600	800	740	DND16E-A	Type C	Applicable
			1800	800	740	DND18E-A	Type C	Applicable
		With cut-out for cable port, R/H side	1400	800	740	DND14F-A	Type C	Applicable
			1600	800	740	DND16F-A	Type C	Applicable
			1800	800	740	DND18F-A	Type C	Applicable
		With cut-out for cable port, R/H and L/H sides	1400	800	740	DND14U-A	Type C	Applicable
			1600	800	740	DND16U-A	Type C	Applicable
			1800	800	740	DND18U-A	Type C	Applicable

		With cut-out for cable port, middle position	1200	800	740	DND12G-A	Type C	Applicable
			1400	800	740	DND14G-A	Type C	Applicable
			1600	800	740	DND16G-A	Type C	Applicable
			1800	800	740	DND18G-A	Type C	Applicable
		With scallop	1200	800	740	DND126-A	Type C	Applicable
			1400	800	740	DND146-A	Type C	Applicable
			1600	800	740	DND166-A	Type C	Applicable
			1800	800	740	DND186-A	Type C	Applicable
	2-desk bench	Plane	1000	1240	740	D2S100-A	Not applicable	Applicable
			1200	1240	740	D2S120-A	Not applicable	Applicable
			1400	1240	740	D2S140-A	Not applicable	Applicable
			1600	1240	740	D2S160-A	Not applicable	Applicable
			1200	1440	740	DNS123-A	Not applicable	Applicable
			1400	1440	740	DNS143-A	Not applicable	Applicable
			1600	1440	740	DNS163-A	Not applicable	Applicable
			1800	1440	740	DNS183-A	Not applicable	Applicable
			1200	1640	740	DNS122-A	Type C	Applicable
			1400	1640	740	DNS142-A	Type C	Applicable
			1600	1640	740	DNS162-A	Type C	Applicable
			1800	1640	740	DNS182-A	Type C	Applicable
			2000	1640	740	DNS202-A	Type C	Applicable
		With grommet, L/H side	1400	1240	740	D2S141-A	Not applicable	Applicable
			1600	1240	740	D2S161-A	Not applicable	Applicable
			1400	1440	740	DNS14H-A	Not applicable	Applicable
			1600	1440	740	DNS16H-A	Not applicable	Applicable
			1800	1440	740	DNS18H-A	Not applicable	Applicable
			1400	1640	740	DNS14N-A	Type C	Applicable
			1600	1640	740	DNS16N-A	Type C	Applicable
			1800	1640	740	DNS18N-A	Type C	Applicable
		With grommet, R/H side	1400	1240	740	D2S142-A	Not applicable	Applicable
			1600	1240	740	D2S162-A	Not applicable	Applicable
			1400	1440	740	DNS14J-A	Not applicable	Applicable
			1600	1440	740	DNS16J-A	Not applicable	Applicable
			1800	1440	740	DNS18J-A	Not applicable	Applicable
			1400	1640	740	DNS14P-A	Type C	Applicable
			1600	1640	740	DNS16P-A	Type C	Applicable
			1800	1640	740	DNS18P-A	Type C	Applicable
		With grommet, middle position	2000	1640	740	DNS20P-A	Type C	Applicable
			1000	1240	740	D2S103-A	Not applicable	Applicable
			1200	1240	740	D2S123-A	Not applicable	Applicable
			1400	1240	740	D2S143-A	Not applicable	Applicable
			1600	1240	740	D2S163-A	Not applicable	Applicable

			1200	1440	740	DNS125-A	Not applicable	Applicable
			1400	1440	740	DNS145-A	Not applicable	Applicable
			1600	1440	740	DNS165-A	Not applicable	Applicable
			1800	1440	740	DNS185-A	Not applicable	Applicable
			1200	1640	740	DNS124-A	Type C	Applicable
			1400	1640	740	DNS144-A	Type C	Applicable
			1600	1640	740	DNS164-A	Type C	Applicable
			1800	1640	740	DNS184-A	Type C	Applicable
			2000	1640	740	DNS204-A	Type C	Applicable
		With cut-out for cable port, L/H side	1400	1240	740	D2S144-A	Not applicable	Applicable
			1600	1240	740	D2S164-A	Not applicable	Applicable
			1400	1440	740	DNS14K-A	Not applicable	Applicable
			1600	1440	740	DNS16K-A	Not applicable	Applicable
			1800	1440	740	DNS18K-A	Not applicable	Applicable
			1400	1640	740	DNS14R-A	Type C	Applicable
			1600	1640	740	DNS16R-A	Type C	Applicable
			1800	1640	740	DNS18R-A	Type C	Applicable
			2000	1640	740	DNS20R-A	Type C	Applicable
		With cut-out for cable port, R/H side	1400	1240	740	D2S145-A	Not applicable	Applicable
			1600	1240	740	D2S165-A	Not applicable	Applicable
			1400	1440	740	DNS14L-A	Not applicable	Applicable
			1600	1440	740	DNS16L-A	Not applicable	Applicable
			1800	1440	740	DNS18L-A	Not applicable	Applicable
			1400	1640	740	DNS14S-A	Type C	Applicable
			1600	1640	740	DNS16S-A	Type C	Applicable
			1800	1640	740	DNS18S-A	Type C	Applicable
			2000	1640	740	DNS20S-A	Type C	Applicable
		With cut-out for cable port, R/H and L/H sides	1400	1240	740	D2S148-A	Not applicable	Applicable
			1600	1240	740	D2S168-A	Not applicable	Applicable
			1400	1440	740	DNS14V-A	Not applicable	Applicable
			1600	1440	740	DNS16V-A	Not applicable	Applicable
			1800	1440	740	DNS18V-A	Not applicable	Applicable
			1400	1640	740	DNS14Z-A	Type C	Applicable
			1600	1640	740	DNS16Z-A	Type C	Applicable
			1800	1640	740	DNS18Z-A	Type C	Applicable
			2000	1640	740	DNS20Z-A	Type C	Applicable
		With cut-out for cable port, middle position	1000	1240	740	D2S106-A	Not applicable	Applicable
			1200	1240	740	D2S126-A	Not applicable	Applicable
			1400	1240	740	D2S146-A	Not applicable	Applicable
			1600	1240	740	D2S166-A	Not applicable	Applicable
			1200	1440	740	DNS12M-A	Not applicable	Applicable

			1400	1440	740	DNS14M-A	Not applicable	Applicable
			1600	1440	740	DNS16M-A	Not applicable	Applicable
			1800	1440	740	DNS18M-A	Not applicable	Applicable
			1200	1640	740	DNS12T-A	Type C	Applicable
			1400	1640	740	DNS14T-A	Type C	Applicable
			1600	1640	740	DNS16T-A	Type C	Applicable
			1800	1640	740	DNS18T-A	Type C	Applicable
			2000	1640	740	DNS20T-A	Type C	Applicable
		With scallop	1000	1240	740	D2S107-A	Not applicable	Applicable
			1200	1240	740	D2S127-A	Not applicable	Applicable
			1400	1240	740	D2S147-A	Not applicable	Applicable
			1600	1240	740	D2S167-A	Not applicable	Applicable
			1200	1440	740	DNS127-A	Not applicable	Applicable
			1400	1440	740	DNS147-A	Not applicable	Applicable
			1600	1440	740	DNS167-A	Not applicable	Applicable
			1800	1440	740	DNS187-A	Not applicable	Applicable
			1200	1640	740	DNS126-A	Type C	Applicable
			1400	1640	740	DNS146-A	Type C	Applicable
			1600	1640	740	DNS166-A	Type C	Applicable
			1800	1640	740	DNS186-A	Type C	Applicable
			2000	1640	740	DNS206-A	Type C	Applicable
	4-desk bench	Plane	2400	1440	740	DNS243-A	Not applicable	Applicable
			2800	1440	740	DNS283-A	Not applicable	Applicable
			3200	1440	740	DNS323-A	Not applicable	Applicable
			3600	1440	740	DNS363-A	Not applicable	Applicable
			2400	1640	740	DNS242-A	Type C	Applicable
			2800	1640	740	DNS282-A	Type C	Applicable
			3200	1640	740	DNS322-A	Type C	Applicable
			3600	1640	740	DNS362-A	Type C	Applicable
		With grommet, L/H side	2800	1440	740	D4S280-A	Not applicable	Applicable
			3200	1440	740	D4S320-A	Not applicable	Applicable
			3600	1440	740	D4S360-A	Not applicable	Applicable
			2800	1640	740	D4S285-A	Type C	Applicable
			3200	1640	740	D4S325-A	Type C	Applicable
			3600	1640	740	D4S365-A	Type C	Applicable
		With grommet, R/H side	2800	1440	740	D4S281-A	Not applicable	Applicable
			3200	1440	740	D4S321-A	Not applicable	Applicable
			3600	1440	740	D4S361-A	Not applicable	Applicable
			2800	1640	740	D4S286-A	Type C	Applicable
			3200	1640	740	D4S326-A	Type C	Applicable
			3600	1640	740	D4S366-A	Type C	Applicable
		With grommet, middle position	2400	1440	740	DNS245-A	Not applicable	Applicable
			2800	1440	740	DNS285-A	Not applicable	Applicable

			3200	1440	740	DNS325-A	Not applicable	Applicable
			3600	1440	740	DNS365-A	Not applicable	Applicable
			2400	1640	740	DNS244-A	Type C	Applicable
			2800	1640	740	DNS284-A	Type C	Applicable
			3200	1640	740	DNS324-A	Type C	Applicable
			3600	1640	740	DNS364-A	Type C	Applicable
		With cut-out for cable port, L/H side	2800	1440	740	D4S282-A	Not applicable	Applicable
			3200	1440	740	D4S322-A	Not applicable	Applicable
			3600	1440	740	D4S362-A	Not applicable	Applicable
			2800	1640	740	D4S287-A	Type C	Applicable
			3200	1640	740	D4S327-A	Type C	Applicable
			3600	1640	740	D4S367-A	Type C	Applicable
		With cut-out for cable port, R/H side	2800	1440	740	D4S283-A	Not applicable	Applicable
			3200	1440	740	D4S323-A	Not applicable	Applicable
			3600	1440	740	D4S363-A	Not applicable	Applicable
			2800	1640	740	D4S288-A	Type C	Applicable
			3200	1640	740	D4S328-A	Type C	Applicable
			3600	1640	740	D4S368-A	Type C	Applicable
		With cut-out for cable port, R/H and L/H sides	2800	1440	740	D4S28A-A	Not applicable	Applicable
			3200	1440	740	D4S32A-A	Not applicable	Applicable
			3600	1440	740	D4S36A-A	Not applicable	Applicable
			2800	1640	740	D4S28B-A	Type C	Applicable
			3200	1640	740	D4S32B-A	Type C	Applicable
			3600	1640	740	D4S36B-A	Type C	Applicable
		With cut-out for cable port, middle position	2400	1440	740	D4S244-A	Not applicable	Applicable
			2800	1440	740	D4S284-A	Not applicable	Applicable
			3200	1440	740	D4S324-A	Not applicable	Applicable
			3600	1440	740	D4S364-A	Not applicable	Applicable
			2400	1640	740	D4S249-A	Type C	Applicable
			2800	1640	740	D4S289-A	Type C	Applicable
			3200	1640	740	D4S329-A	Type C	Applicable
			3600	1640	740	D4S369-A	Type C	Applicable
		With scallop	2400	1440	740	DNS249-A	Not applicable	Applicable
			2800	1440	740	DNS289-A	Not applicable	Applicable
			3200	1440	740	DNS329-A	Not applicable	Applicable
			3600	1440	740	DNS369-A	Not applicable	Applicable
			2400	1640	740	DNS247-A	Type C	Applicable
			2800	1640	740	DNS287-A	Type C	Applicable
			3200	1640	740	DNS327-A	Type C	Applicable
			3600	1640	740	DNS367-A	Type C	Applicable
	End of bench desk	Plane	1240	600	740	DNE120-A	Not applicable	Applicable
			1440	700	740	DNE140-A	Not applicable	Applicable
			1640	800	740	DNE160-A	Type C	Applicable
		With grommet, L/H side	1440	700	740	DNE141-A	Not applicable	Applicable
			1640	800	740	DNE161-A	Type C	Applicable
		With grommet, R/H side	1440	700	740	DNE142-A	Not applicable	Applicable

			1640	800	740	DNE162-A	Type C	Applicable
		With grommet, middle position	1240	600	740	DNE123-A	Not applicable	Applicable
			1440	700	740	DNE143-A	Not applicable	Applicable
			1640	800	740	DNE163-A	Type C	Applicable
		With cut-out for cable port, L/H side	1440	700	740	DNE144-A	Not applicable	Applicable
			1640	800	740	DNE164-A	Type C	Applicable
		With cut-out for cable port, R/H side	1440	700	740	DNE145-A	Not applicable	Applicable
			1640	800	740	DNE165-A	Type C	Applicable
		With cut-out for cable port, R/H and L/H sides	1440	700	740	DNE148-A	Not applicable	Applicable
			1640	800	740	DNE168-A	Type C	Applicable
		With cut-out for cable port, middle position	1240	600	740	DNE126-A	Not applicable	Applicable
			1440	700	740	DNE146-A	Not applicable	Applicable
			1640	800	740	DNE166-A	Type C	Applicable
		With scallop	1240	600	740	DNE127-A	Not applicable	Applicable
			1440	700	740	DNE147-A	Not applicable	Applicable
			1640	800	740	DNE167-A	Type C	Applicable
	Crescent desk	Plane, L/H side	1400	1200	740	DNL140-A	Type C	Applicable
			1600	1200	740	DNL160-A	Type C	Applicable
			1800	1200	740	DNL180-A	Type C	Applicable
		With grommet, L/H side	1400	1200	740	DNL141-A	Type C	Applicable
			1600	1200	740	DNL161-A	Type C	Applicable
			1800	1200	740	DNL181-A	Type C	Applicable
		With cut-out for cable port, L/H side	1400	1200	740	DNL144-A	Type C	Applicable
			1600	1200	740	DNL164-A	Type C	Applicable
			1800	1200	740	DNL184-A	Type C	Applicable
		Plane, R/H side	1400	1200	740	DNR140-A	Type C	Applicable
			1600	1200	740	DNR160-A	Type C	Applicable
			1800	1200	740	DNR180-A	Type C	Applicable
		With grommet, R/H side	1400	1200	740	DNR141-A	Type C	Applicable
			1600	1200	740	DNR161-A	Type C	Applicable
			1800	1200	740	DNR181-A	Type C	Applicable
		With cut-out for cable port, R/H side	1400	1200	740	DNR144-A	Type C	Applicable
			1600	1200	740	DNR164-A	Type C	Applicable
			1800	1200	740	DNR184-A	Type C	Applicable
	Supplementary unit - return table (edge w=600 mm)	-	800	600	740	DNC080-A	Not applicable	Applicable

Office desking								
NOVA O								
Example	Description	Desktop type	Dimensions, mm			Item	EN 527-1	EN 527-2
			Width	Depth	Height			
	Desk	Plane	1000	600	740	DNA104-O	Not applicable	Applicable
			1200	600	740	DNA124-O	Not applicable	Applicable
			1400	600	740	DNA144-O	Not applicable	Applicable
			1600	600	740	DNA164-O	Not applicable	Applicable
			1200	700	740	DNA122-O	Not applicable	Applicable
			1400	700	740	DNA142-O	Not applicable	Applicable
			1600	700	740	DNA162-O	Not applicable	Applicable
			1800	700	740	DNA182-O	Not applicable	Applicable
			1200	800	740	DNA120-O	Type C	Applicable
			1400	800	740	DNA140-O	Type C	Applicable
			1600	800	740	DNA160-O	Type C	Applicable
			1800	800	740	DNA180-O	Type C	Applicable
			2000	800	740	DNA200-O	Type C	Applicable
		With grommet, L/H side	1400	600	740	DNA14E-O	Not applicable	Applicable
			1600	600	740	DNA16E-O	Not applicable	Applicable
			1400	700	740	DNA14M-O	Not applicable	Applicable
			1600	700	740	DNA16M-O	Not applicable	Applicable
			1800	700	740	DNA18M-O	Not applicable	Applicable
			1400	800	740	DNA14T-O	Type C	Applicable
			1600	800	740	DNA16T-O	Type C	Applicable
			1800	800	740	DNA18T-O	Type C	Applicable
			2000	800	740	DNA20T-O	Type C	Applicable
		With grommet, R/H side	1400	600	740	DNA14F-O	Not applicable	Applicable
			1600	600	740	DNA16F-O	Not applicable	Applicable
			1400	700	740	DNA14N-O	Not applicable	Applicable
			1600	700	740	DNA16N-O	Not applicable	Applicable
			1800	700	740	DNA18N-O	Not applicable	Applicable
			1400	800	740	DNA14U-O	Type C	Applicable
			1600	800	740	DNA16U-O	Type C	Applicable
			1800	800	740	DNA18U-O	Type C	Applicable
			2000	800	740	DNA20U-O	Type C	Applicable
		With grommet, middle position	1000	600	740	DNA10G-O	Not applicable	Applicable
			1200	600	740	DNA12G-O	Not applicable	Applicable
			1400	600	740	DNA14G-O	Not applicable	Applicable
			1600	600	740	DNA16G-O	Not applicable	Applicable
			1200	700	740	DNA123-O	Not applicable	Applicable
			1400	700	740	DNA143-O	Not applicable	Applicable
			1600	700	740	DNA163-O	Not applicable	Applicable
			1800	700	740	DNA183-O	Not applicable	Applicable
			1200	800	740	DNA121-O	Type C	Applicable

			1400	800	740	DNA141-O	Type C	Applicable
			1600	800	740	DNA161-O	Type C	Applicable
			1800	800	740	DNA181-O	Type C	Applicable
			2000	800	740	DNA201-O	Type C	Applicable
	With cut-out for cable port, L/H side	1400	600	740	DNA14H-O	Not applicable		Applicable
		1600	600	740	DNA16H-O	Not applicable		Applicable
		1400	700	740	DNA14P-O	Not applicable		Applicable
		1600	700	740	DNA16P-O	Not applicable		Applicable
		1800	700	740	DNA18P-O	Not applicable		Applicable
		1400	800	740	DNA14V-O	Type C		Applicable
		1600	800	740	DNA16V-O	Type C		Applicable
		1800	800	740	DNA18V-O	Type C		Applicable
		2000	800	740	DNA20V-O	Type C		Applicable
	With cut-out for cable port, R/H side	1400	600	740	DNA14J-O	Not applicable		Applicable
		1600	600	740	DNA16J-O	Not applicable		Applicable
		1400	700	740	DNA14R-O	Not applicable		Applicable
		1600	700	740	DNA16R-O	Not applicable		Applicable
		1800	700	740	DNA18R-O	Not applicable		Applicable
		1400	800	740	DNA14Y-O	Type C		Applicable
		1600	800	740	DNA16Y-O	Type C		Applicable
		1800	800	740	DNA18Y-O	Type C		Applicable
		2000	800	740	DNA20Y-O	Type C		Applicable
	With cut-out for cable port, R/H and L/H sides	1400	600	740	DNA14X-O	Not applicable		Applicable
		1600	600	740	DNA16X-O	Not applicable		Applicable
		1400	700	740	DNA14W-O	Not applicable		Applicable
		1600	700	740	DNA16W-O	Not applicable		Applicable
		1800	700	740	DNA18W-O	Not applicable		Applicable
		1400	800	740	DNA14Q-O	Type C		Applicable
		1600	800	740	DNA16Q-O	Type C		Applicable
		1800	800	740	DNA18Q-O	Type C		Applicable
		2000	800	740	DNA20Q-O	Type C		Applicable
	With cut-out for cable port, middle position	1000	600	740	DNA10K-O	Not applicable		Applicable
		1200	600	740	DNA12K-O	Not applicable		Applicable
		1400	600	740	DNA14K-O	Not applicable		Applicable
		1600	600	740	DNA16K-O	Not applicable		Applicable
		1200	700	740	DNA12S-O	Not applicable		Applicable
		1400	700	740	DNA14S-O	Not applicable		Applicable
		1600	700	740	DNA16S-O	Not applicable		Applicable
		1800	700	740	DNA18S-O	Not applicable		Applicable
		1200	800	740	DNA12Z-O	Type C		Applicable
		1400	800	740	DNA14Z-O	Type C		Applicable
		1600	800	740	DNA16Z-O	Type C		Applicable
		1800	800	740	DNA18Z-O	Type C		Applicable
		2000	800	740	DNA20Z-O	Type C		Applicable
	With scallop	1000	600	740	DNA10L-O	Not applicable		Applicable

			1200	600	740	DNA12L-O	Not applicable	Applicable
			1400	600	740	DNA14L-O	Not applicable	Applicable
			1600	600	740	DNA16L-O	Not applicable	Applicable
			1200	700	740	DNA126-O	Not applicable	Applicable
			1400	700	740	DNA146-O	Not applicable	Applicable
			1600	700	740	DNA166-O	Not applicable	Applicable
			1800	700	740	DNA186-O	Not applicable	Applicable
			1200	800	740	DNA125-O	Type C	Applicable
			1400	800	740	DNA145-O	Type C	Applicable
			1600	800	740	DNA165-O	Type C	Applicable
			1800	800	740	DNA185-O	Type C	Applicable
			2000	800	740	DNA205-O	Type C	Applicable
	Single row 2-desk bench	Plane	2400	800	740	DNS240-O	Type C	Applicable
			2800	800	740	DNS280-O	Type C	Applicable
			3200	800	740	DNS320-O	Type C	Applicable
			3600	800	740	DNS360-O	Type C	Applicable
		With grommet, L/H side	2800	800	740	DNS28C-O	Type C	Applicable
			3200	800	740	DNS32C-O	Type C	Applicable
			3600	800	740	DNS36C-O	Type C	Applicable
		With grommet, R/H side	2800	800	740	DNS28D-O	Type C	Applicable
			3200	800	740	DNS32D-O	Type C	Applicable
			3600	800	740	DNS36D-O	Type C	Applicable
		With grommet, middle position	2400	800	740	DNS241-O	Type C	Applicable
			2800	800	740	DNS281-O	Type C	Applicable
			3200	800	740	DNS321-O	Type C	Applicable
			3600	800	740	DNS361-O	Type C	Applicable
		With cut-out for cable port, L/H side	2800	800	740	DNS28E-O	Type C	Applicable
			3200	800	740	DNS32E-O	Type C	Applicable
			3600	800	740	DNS36E-O	Type C	Applicable
		With cut-out for cable port, R/H side	2800	800	740	DNS28F-O	Type C	Applicable
			3200	800	740	DNS32F-O	Type C	Applicable
			3600	800	740	DNS36F-O	Type C	Applicable
		With cut-out for cable port, R/H and L/H sides	2800	800	740	DNS28U-O	Type C	Applicable
			3200	800	740	DNS32U-O	Type C	Applicable
			3600	800	740	DNS36U-O	Type C	Applicable
		With cut-out for cable port, middle position	2400	800	740	DNS24G-O	Type C	Applicable
			2800	800	740	DNS28G-O	Type C	Applicable
			3200	800	740	DNS32G-O	Type C	Applicable
			3600	800	740	DNS36G-O	Type C	Applicable
		With scallop	2400	800	740	DNS246-O	Type C	Applicable
			2800	800	740	DNS286-O	Type C	Applicable
			3200	800	740	DNS326-O	Type C	Applicable
			3600	800	740	DNS366-O	Type C	Applicable
	Supplementary unit for single row 2-desk bench	Plane	1200	800	740	DND120-O	Type C	Applicable
			1400	800	740	DND140-O	Type C	Applicable
			1600	800	740	DND160-O	Type C	Applicable
			1800	800	740	DND180-O	Type C	Applicable
		With grommet, L/H side	1400	800	740	DND14C-O	Type C	Applicable
			1600	800	740	DND16C-O	Type C	Applicable
			1800	800	740	DND18C-O	Type C	Applicable
		With grommet, R/H side	1400	800	740	DND14D-O	Type C	Applicable
			1600	800	740	DND16D-O	Type C	Applicable

			1800	800	740	DND18D-O	Type C	Applicable
		With grommet, middle position	1200	800	740	DND121-O	Type C	Applicable
			1400	800	740	DND141-O	Type C	Applicable
			1600	800	740	DND161-O	Type C	Applicable
			1800	800	740	DND181-O	Type C	Applicable
		With cut-out for cable port, L/H side	1400	800	740	DND14E-O	Type C	Applicable
			1600	800	740	DND16E-O	Type C	Applicable
			1800	800	740	DND18E-O	Type C	Applicable
		With cut-out for cable port, R/H side	1400	800	740	DND14F-O	Type C	Applicable
			1600	800	740	DND16F-O	Type C	Applicable
			1800	800	740	DND18F-O	Type C	Applicable
		With cut-out for cable port, R/H and L/H sides	1400	800	740	DND14U-O	Type C	Applicable
			1600	800	740	DND16U-O	Type C	Applicable
			1800	800	740	DND18U-O	Type C	Applicable
		With cut-out for cable port, middle position	1200	800	740	DND12G-O	Type C	Applicable
			1400	800	740	DND14G-O	Type C	Applicable
			1600	800	740	DND16G-O	Type C	Applicable
			1800	800	740	DND18G-O	Type C	Applicable
		With scallop	1200	800	740	DND126-O	Type C	Applicable
			1400	800	740	DND146-O	Type C	Applicable
			1600	800	740	DND166-O	Type C	Applicable
			1800	800	740	DND186-O	Type C	Applicable
	2-desk bench	Plane	1000	1240	740	D2S100-O	Not applicable	Applicable
			1200	1240	740	D2S120-O	Not applicable	Applicable
			1400	1240	740	D2S140-O	Not applicable	Applicable
			1600	1240	740	D2S160-O	Not applicable	Applicable
			1200	1440	740	DNS123-O	Not applicable	Applicable
			1400	1440	740	DNS143-O	Not applicable	Applicable
			1600	1440	740	DNS163-O	Not applicable	Applicable
			1800	1440	740	DNS183-O	Not applicable	Applicable
			1200	1640	740	DNS122-O	Type C	Applicable
			1400	1640	740	DNS142-O	Type C	Applicable
			1600	1640	740	DNS162-O	Type C	Applicable
			1800	1640	740	DNS182-O	Type C	Applicable
			2000	1640	740	DNS202-O	Type C	Applicable
		With grommet, L/H side	1400	1240	740	D2S141-O	Not applicable	Applicable
			1600	1240	740	D2S161-O	Not applicable	Applicable
			1400	1440	740	DNS14H-O	Not applicable	Applicable
			1600	1440	740	DNS16H-O	Not applicable	Applicable
			1800	1440	740	DNS18H-O	Not applicable	Applicable
			1400	1640	740	DNS14N-O	Type C	Applicable
			1600	1640	740	DNS16N-O	Type C	Applicable
			1800	1640	740	DNS18N-O	Type C	Applicable
		With grommet, R/H side	2000	1640	740	DNS20N-O	Type C	Applicable
			1400	1240	740	D2S142-O	Not applicable	Applicable
			1600	1240	740	D2S162-O	Not applicable	Applicable
			1400	1440	740	DNS14J-O	Not applicable	Applicable
			1600	1440	740	DNS16J-O	Not applicable	Applicable

			1800	1440	740	DNS18J-O	Not applicable	Applicable
			1400	1640	740	DNS14P-O	Type C	Applicable
			1600	1640	740	DNS16P-O	Type C	Applicable
			1800	1640	740	DNS18P-O	Type C	Applicable
			2000	1640	740	DNS20P-O	Type C	Applicable
		With grommet, middle position	1000	1240	740	D2S103-O	Not applicable	Applicable
			1200	1240	740	D2S123-O	Not applicable	Applicable
			1400	1240	740	D2S143-O	Not applicable	Applicable
			1600	1240	740	D2S163-O	Not applicable	Applicable
			1200	1440	740	DNS125-O	Not applicable	Applicable
			1400	1440	740	DNS145-O	Not applicable	Applicable
			1600	1440	740	DNS165-O	Not applicable	Applicable
			1800	1440	740	DNS185-O	Not applicable	Applicable
			1200	1640	740	DNS124-O	Type C	Applicable
			1400	1640	740	DNS144-O	Type C	Applicable
			1600	1640	740	DNS164-O	Type C	Applicable
			1800	1640	740	DNS184-O	Type C	Applicable
			2000	1640	740	DNS204-O	Type C	Applicable
		With cut-out for cable port, L/H side	1400	1240	740	D2S144-O	Not applicable	Applicable
			1600	1240	740	D2S164-O	Not applicable	Applicable
			1400	1440	740	DNS14K-O	Not applicable	Applicable
			1600	1440	740	DNS16K-O	Not applicable	Applicable
			1800	1440	740	DNS18K-O	Not applicable	Applicable
			1400	1640	740	DNS14R-O	Type C	Applicable
			1600	1640	740	DNS16R-O	Type C	Applicable
			1800	1640	740	DNS18R-O	Type C	Applicable
			2000	1640	740	DNS20R-O	Type C	Applicable
		With cut-out for cable port, R/H side	1400	1240	740	D2S145-O	Not applicable	Applicable
			1600	1240	740	D2S165-O	Not applicable	Applicable
			1400	1440	740	DNS14L-O	Not applicable	Applicable
			1600	1440	740	DNS16L-O	Not applicable	Applicable
			1800	1440	740	DNS18L-O	Not applicable	Applicable
			1400	1640	740	DNS14S-O	Type C	Applicable
			1600	1640	740	DNS16S-O	Type C	Applicable
			1800	1640	740	DNS18S-O	Type C	Applicable
			2000	1640	740	DNS20S-O	Type C	Applicable
		With cut-out for cable port, R/H and L/H sides	1400	1240	740	D2S148-O	Not applicable	Applicable
			1600	1240	740	D2S168-O	Not applicable	Applicable
			1400	1440	740	DNS14V-O	Not applicable	Applicable
			1600	1440	740	DNS16V-O	Not applicable	Applicable
			1800	1440	740	DNS18V-O	Not applicable	Applicable
			1400	1640	740	DNS14Z-O	Type C	Applicable
			1600	1640	740	DNS16Z-O	Type C	Applicable
			1800	1640	740	DNS18Z-O	Type C	Applicable
			2000	1640	740	DNS20Z-O	Type C	Applicable

		With cut-out for cable port, middle position	1000	1240	740	D2S106-O	Not applicable	Applicable
			1200	1240	740	D2S126-O	Not applicable	Applicable
			1400	1240	740	D2S146-O	Not applicable	Applicable
			1600	1240	740	D2S166-O	Not applicable	Applicable
			1200	1440	740	DNS12M-O	Not applicable	Applicable
			1400	1440	740	DNS14M-O	Not applicable	Applicable
			1600	1440	740	DNS16M-O	Not applicable	Applicable
			1800	1440	740	DNS18M-O	Not applicable	Applicable
			1200	1640	740	DNS12T-O	Type C	Applicable
			1400	1640	740	DNS14T-O	Type C	Applicable
			1600	1640	740	DNS16T-O	Type C	Applicable
			1800	1640	740	DNS18T-O	Type C	Applicable
			2000	1640	740	DNS20T-O	Type C	Applicable
		With scallop	1000	1240	740	D2S107-O	Not applicable	Applicable
			1200	1240	740	D2S127-O	Not applicable	Applicable
			1400	1240	740	D2S147-O	Not applicable	Applicable
			1600	1240	740	D2S167-O	Not applicable	Applicable
			1200	1440	740	DNS127-O	Not applicable	Applicable
			1400	1440	740	DNS147-O	Not applicable	Applicable
			1600	1440	740	DNS167-O	Not applicable	Applicable
			1800	1440	740	DNS187-O	Not applicable	Applicable
			1200	1640	740	DNS126-O	Type C	Applicable
			1400	1640	740	DNS146-O	Type C	Applicable
			1600	1640	740	DNS166-O	Type C	Applicable
			1800	1640	740	DNS186-O	Type C	Applicable
			2000	1640	740	DNS206-O	Type C	Applicable
	4-desk bench	Plane	2400	1440	740	DNS243-O	Not applicable	Applicable
			2800	1440	740	DNS283-O	Not applicable	Applicable
			3200	1440	740	DNS323-O	Not applicable	Applicable
			3600	1440	740	DNS363-O	Not applicable	Applicable
			2400	1640	740	DNS242-O	Type C	Applicable
			2800	1640	740	DNS282-O	Type C	Applicable
			3200	1640	740	DNS322-O	Type C	Applicable
			3600	1640	740	DNS362-O	Type C	Applicable
		With grommet, L/H side	2800	1440	740	D4S280-O	Not applicable	Applicable
			3200	1440	740	D4S320-O	Not applicable	Applicable
			3600	1440	740	D4S360-O	Not applicable	Applicable
			2800	1640	740	D4S285-O	Type C	Applicable
			3200	1640	740	D4S325-O	Type C	Applicable
			3600	1640	740	D4S365-O	Type C	Applicable
		With grommet, R/H side	2800	1440	740	D4S281-O	Not applicable	Applicable
			3200	1440	740	D4S321-O	Not applicable	Applicable
			3600	1440	740	D4S361-O	Not applicable	Applicable
			2800	1640	740	D4S286-O	Type C	Applicable

			3200	1640	740	D4S326-O	Type C	Applicable
			3600	1640	740	D4S366-O	Type C	Applicable
		With grommet, middle position	2400	1440	740	DNS245-O	Not applicable	Applicable
			2800	1440	740	DNS285-O	Not applicable	Applicable
			3200	1440	740	DNS325-O	Not applicable	Applicable
			3600	1440	740	DNS365-O	Not applicable	Applicable
			2400	1640	740	DNS244-O	Type C	Applicable
			2800	1640	740	DNS284-O	Type C	Applicable
			3200	1640	740	DNS324-O	Type C	Applicable
			3600	1640	740	DNS364-O	Type C	Applicable
		With cut-out for cable port, L/H side	2800	1440	740	D4S282-O	Not applicable	Applicable
			3200	1440	740	D4S322-O	Not applicable	Applicable
			3600	1440	740	D4S362-O	Not applicable	Applicable
			2800	1640	740	D4S287-O	Type C	Applicable
			3200	1640	740	D4S327-O	Type C	Applicable
			3600	1640	740	D4S367-O	Type C	Applicable
		With cut-out for cable port, R/H side	2800	1440	740	D4S283-O	Not applicable	Applicable
			3200	1440	740	D4S323-O	Not applicable	Applicable
			3600	1440	740	D4S363-O	Not applicable	Applicable
			2800	1640	740	D4S288-O	Type C	Applicable
			3200	1640	740	D4S328-O	Type C	Applicable
			3600	1640	740	D4S368-O	Type C	Applicable
		With cut-out for cable port, R/H and L/H sides	2800	1440	740	D4S28A-O	Not applicable	Applicable
			3200	1440	740	D4S32A-O	Not applicable	Applicable
			3600	1440	740	D4S36A-O	Not applicable	Applicable
			2800	1640	740	D4S28B-O	Type C	Applicable
			3200	1640	740	D4S32B-O	Type C	Applicable
			3600	1640	740	D4S36B-O	Type C	Applicable
		With cut-out for cable port, middle position	2400	1440	740	D4S244-O	Not applicable	Applicable
			2800	1440	740	D4S284-O	Not applicable	Applicable
			3200	1440	740	D4S324-O	Not applicable	Applicable
			3600	1440	740	D4S364-O	Not applicable	Applicable
			2400	1640	740	D4S249-O	Type C	Applicable
			2800	1640	740	D4S289-O	Type C	Applicable
			3200	1640	740	D4S329-O	Type C	Applicable
			3600	1640	740	D4S369-O	Type C	Applicable
		With scallop	2400	1440	740	DNS249-O	Not applicable	Applicable
			2800	1440	740	DNS289-O	Not applicable	Applicable
			3200	1440	740	DNS329-O	Not applicable	Applicable
			3600	1440	740	DNS369-O	Not applicable	Applicable
			2400	1640	740	DNS247-O	Type C	Applicable
			2800	1640	740	DNS287-O	Type C	Applicable
			3200	1640	740	DNS327-O	Type C	Applicable
			3600	1640	740	DNS367-O	Type C	Applicable
	End of bench desk	Plane	1240	600	740	DNE120-O	Not applicable	Applicable

			1440	700	740	DNE140-O	Not applicable	Applicable
			1640	800	740	DNE160-O	Type C	Applicable
		With grommet, L/H side	1440	700	740	DNE141-O	Not applicable	Applicable
			1640	800	740	DNE161-O	Type C	Applicable
		With grommet, R/H side	1440	700	740	DNE142-O	Not applicable	Applicable
			1640	800	740	DNE162-O	Type C	Applicable
		With grommet, middle position	1240	600	740	DNE123-O	Not applicable	Applicable
			1440	700	740	DNE143-O	Not applicable	Applicable
			1640	800	740	DNE163-O	Type C	Applicable
		With cut-out for cable port, L/H side	1440	700	740	DNE144-O	Not applicable	Applicable
			1640	800	740	DNE164-O	Type C	Applicable
		With cut-out for cable port, R/H side	1440	700	740	DNE145-O	Not applicable	Applicable
			1640	800	740	DNE165-O	Type C	Applicable
		With cut-out for cable port, R/H and L/H sides	1440	700	740	DNE148-O	Not applicable	Applicable
			1640	800	740	DNE168-O	Type C	Applicable
		With cut-out for cable port, middle position	1240	600	740	DNE126-O	Not applicable	Applicable
			1440	700	740	DNE146-O	Not applicable	Applicable
			1640	800	740	DNE166-O	Type C	Applicable
		With scallop	1240	600	740	DNE127-O	Not applicable	Applicable
			1440	700	740	DNE147-O	Not applicable	Applicable
			1640	800	740	DNE167-O	Type C	Applicable
	Crescent desk	Plane, L/H side	1400	1200	740	DNL140-O	Type C	Applicable
			1600	1200	740	DNL160-O	Type C	Applicable
			1800	1200	740	DNL180-O	Type C	Applicable
		With grommet, L/H side	1400	1200	740	DNL141-O	Type C	Applicable
			1600	1200	740	DNL161-O	Type C	Applicable
			1800	1200	740	DNL181-O	Type C	Applicable
		With cut-out for cable port, L/H side	1400	1200	740	DNL144-O	Type C	Applicable
			1600	1200	740	DNL164-O	Type C	Applicable
			1800	1200	740	DNL184-O	Type C	Applicable
		Plane, R/H side	1400	1200	740	DNR140-O	Type C	Applicable
			1600	1200	740	DNR160-O	Type C	Applicable
			1800	1200	740	DNR180-O	Type C	Applicable
		With grommet, R/H side	1400	1200	740	DNR141-O	Type C	Applicable
			1600	1200	740	DNR161-O	Type C	Applicable
			1800	1200	740	DNR181-O	Type C	Applicable
		With cut-out for cable port, R/H side	1400	1200	740	DNR144-O	Type C	Applicable
			1600	1200	740	DNR164-O	Type C	Applicable
			1800	1200	740	DNR184-O	Type C	Applicable
	Supplementary unit - return table (edge w=600 mm)	-	800	600	740	DNC080-O	Not applicable	Applicable

Office desking								
NOVA H								
Example	Description	Desktop type	Dimensions, mm			Item	EN 527-1	EN 527-2
			Width	Depth	Height			
	Selectable height desk	Plane	1200	800	620 - 850	DNA120-UH	Type B	Applicable
			1400	800	620 - 850	DNA140-UH	Type B	Applicable
			1600	800	620 - 850	DNA160-UH	Type B	Applicable
			1800	800	620 - 850	DNA180-UH	Type B	Applicable
		With grommet, L/H side	1400	800	620 - 850	DNA14T-UH	Type B	Applicable
			1600	800	620 - 850	DNA16T-UH	Type B	Applicable
			1800	800	620 - 850	DNA18T-UH	Type B	Applicable
		With grommet, R/H side	1400	800	620 - 850	DNA14U-UH	Type B	Applicable
			1600	800	620 - 850	DNA16U-UH	Type B	Applicable
			1800	800	620 - 850	DNA18U-UH	Type B	Applicable
		With grommet, middle position	1200	800	620 - 850	DNA121-UH	Type B	Applicable
			1400	800	620 - 850	DNA141-UH	Type B	Applicable
			1600	800	620 - 850	DNA161-UH	Type B	Applicable
			1800	800	620 - 850	DNA181-UH	Type B	Applicable
		With cut-out for cable port, L/H side	1400	800	620 - 850	DNA14V-UH	Type B	Applicable
			1600	800	620 - 850	DNA16V-UH	Type B	Applicable
			1800	800	620 - 850	DNA18V-UH	Type B	Applicable
		With cut-out for cable port, R/H side	1400	800	620 - 850	DNA14Y-UH	Type B	Applicable
			1600	800	620 - 850	DNA16Y-UH	Type B	Applicable
			1800	800	620 - 850	DNA18Y-UH	Type B	Applicable
		With cut-out for cable port, R/H and L/H sides	1400	800	620-850	DNA14Q-UH	Type B	Applicable
			1600	800	620-850	DNA16Q-UH	Type B	Applicable
			1800	800	620-850	DNA18Q-UH	Type B	Applicable
		With cut-out for cable port, middle position	1200	800	620 - 850	DNA12Z-UH	Type B	Applicable
			1400	800	620 - 850	DNA14Z-UH	Type B	Applicable
			1600	800	620 - 850	DNA16Z-UH	Type B	Applicable
			1800	800	620 - 850	DNA18Z-UH	Type B	Applicable
		With scallop	1200	800	620 - 850	DNA125-UH	Type B	Applicable
			1400	800	620 - 850	DNA145-UH	Type B	Applicable
			1600	800	620 - 850	DNA165-UH	Type B	Applicable
			1800	800	620 - 850	DNA185-UH	Type B	Applicable